



MODELS NOS. SPECIFICATIONS	Metrix+ DT 2234B Photo Tachometer	Metrix+ DT 2235B Contact Tachometer	Metrix+ TM 4005 Photo-Contact Tachometer
Measuring Range-Photo Contact Linear Rolling Speed (Surface Speed)	2.5~99999RPM	0.5~19,999RPM 0.05~1999.9m/min 0.2~6560Ft/min	2.5~99999RPM Photo 2.5~19,999RPM Contact 0.05~1999.9m/min 0.2~6560Ft/min
Resolution	0.1RPM、1RPM	0.1RPM、1RPM 0.01m/min、0.1m/min 1Ft/min	0.1RPM、1RPM 0.1RPM、1RPM 0.01m/min、0.1m/min 1Ft/min
Accuracy	±(0.05%+1 word)	±(0.05%+1 word)	±(0.05%+1 word)
Sampling Frequency	0.8Sec	0.8Sec	0.8Sec
Max & Min Data Function	√	√	√
Provide Probe	---	√	√
Low Battery Indication	√	√	√
Measuring Mode	photoelectric type	Contact Type	Photoelectric + Contact type
Data Hold	√	√	---
LCD Backlight	√	√	---
Operating Temperature	0~50°C	0~50°C	0~50°C
Storing Temperature	-20~60°C	-20~60°C	-20~60°C
PACKING INFORMATION			
Power	AAA*3 battery	AAA*3 battery	AA*4 battery
Product Net Weight	120g	150g	280g
Product Size	150*56*31mm	155*55*35mm	215*74*32mm
Packing	Gift box	Gift box	Gift box